


Vicoll DATA SHEET

Connecto® I Light grey shallow channel - Outside width 130 mm - with PVC grating light grey color class A15

Code: CAB510APG







■ FUNCTION:

The drainage channel is designed to drain run-off water. In accordance with EN1433 standard and the marking CE, it can be used in private areas for all building applications, the environment of home, parks and gardens in class A15.

■ DESCRIPTION:

It consists of:

- an injected PVC body in light grey colour with male/female interlocking system
- one PVC grating light grey class A15



STCAN

■ ACCESSORIES:

The network connection can be realized thanks to the following PVC accessories:

- end cap/end or lateral outlet Ø 40: NAH773
- vertical outlet Ø 100 or 110: STCAN or SVCAN
- sump unit with outlet Ø 100 or 110: PSCVT or PSCVV



■ CHARACTERISTICS:

Resistance class: A15 Effective width: 98 mm Effective depth: 34 mm Grating type: PVC light grey Drainage surface: 232 cm²/ml Hydraulic section: 33 cm²

Opening dimensions: less than 8 mm

Weight: 1,2 kg





■ IMPLEMENTATION:

- 1. The channel body makes it possible to carry out 90° angles by interlocking.
- 2. See the scheme opposite

Bituminous Paved area area Concrete C20/25

■ QUALITY - ENVIRONMENT:



DATE: Fedruary 2016



Head office and Plants: 37, rue Pierre et Marie Curie - BP 10966 - 49309 CHOLET Cedex

Email: export.nicoll@aliaxis.com

NON CONTRACTUAL DOCUMENT

an OAliaxis company